

FOREST SHUTTLE® & FMS® Series


The Forest Shuttle[®] curtain motor and the Forest Motorised curtain track System (FMS[®]) make an unbeatable combination when it comes to a troublefree operated electric curtains.

FOREST SHUTTLE® S FOREST SHUTTLE® M FOREST SHUTTLE® L FOREST SHUTTLE® AC FOREST SHUTTLE® iOn FOREST FMS[®] FOREST FMS[®] Plus FOREST FMS[®] Plus Recess FOREST FMS[®] Dual

THE WORLD BEHIND YOUR CURTAINS



FOREST SHUTTLE® Series



When it comes to comfort, the Forest Shuttle[®] lives up to its expectations. Being able to open and close your curtains remotely, from the comfort of your chair, when you are on holiday, automatically at pre-programmed opening and closing times or even linked to variable sunrise and sunset times. The Forest Shuttle[®] is the silent force behind the opening and closing of curtains all over the world.

The Shuttle[®] can be fully integrated in all major home automation systems.

For maximum safety, integrated emergency control ensures manual operation of the drapery in case of power failure.

The smooth and silent running curtain track system can, in addition to remote operation, also be operated by hand. Thanks to Touch Control technology, a gentle pull on the curtain is enough to activate the motor.



PRODUCT INFORMATION

The Forest Shuttle[®] family of motors offer the following functions:

- High quality, extremely reliable and ultra silent motor.
- Integrated RF multi receiver, for Diamond Sense Remote control or wall switch.
- Various control options: App control, Remote Control (RF), Wall Switch Domotics, Building/Hotel Automation, Serial Communication, Z-Wave etc.
- Full automatic setting of the limits.
- Programming of intermediate positions possible.
- Touch Control Technology, gently pulling the curtain by hand will activate the motor. Sensitivity adjustable (except for the Shuttle[®] AC).
- Integrated Emergency Control with automatic declutch in case of power failure, to ensure a manual operation of the curtains.
- Stack-back position programmable to every desired setting;
- Can be used in combination with various motorised track systems like Forest Motorised Track System (standard option), FMS Dual Channel system, Motorised Design System (DS-XL LED) and Motorised Rod System (MRS).
- Can be mounted on the left or the right side of the track.
- Can be used with curved Forest motorised track systems.
- Integrated Z-Wave Plus as option (only Shuttle[®] S/M/L).
- For Skylight System (FSS[®]) a special Shuttle[®] M motor with receiver and fixed drive is available.
- Tandem motor application possible as well.
- Upside down inverted motor mounting available.
- Variable velocity with slow start and slow stop.
- Warranty: 10 years on motor (2 years on battery pack iOn)



FOREST SHUTTLE® SERIES

The Forest Shuttle[®] is offered in 5 versions. Choose which Forest Shuttle motor best suits your application integration needs:



DECORATIVE TRACK OPTIONS

The whole range of Forest motors' are totally compatible throughout our electrically operated curtain track range including the decorative options like the DS-XL[®] LED motorised system and the Motorised Rod System (MRS[®]).





SMART HOME DEMO SUITCASE

We have redesigned our demo case for motorised systems. Besides samples of our standard motorised curtain track system, FMS[®], and the FMS[®] Plus with recess profile, you will also find the new two-channel system, FMS[®] Dual, and our motorised rod system, MRS[®]. Easily demonstrate app operation thanks to the included WiFi dongle and the Wireless Connector. All other operating modes, accessories and documentation are of course included.



FOREST SHUTTLE® iOn



Our bestselling Forest Shuttle[®] system is also available in a wireless, battery powered version. The Shuttle[®] iOn is perfect for areas without nearby power points.

An extensive period of research, development and endurance testing on countless of track set-ups has resulted in the Forest Shuttle® iOn. The Shuttle® iOn's motor is fitted with an internal, removable heavy duty battery pack. Depending on the track size and curtain weight, the battery only needs to be charged 2 to 3 times per year.

You can expect the same unique functionalities as that of the wired Shuttle[®] L, like Touch Control technology. The motor has an integrated Multi RF receiver, allowing for operation using any Forest remote control option.

Unique in the market

The Shuttle[®] iOn can be used in combination with curved tracks (max. 2 bends), which is unique in the market. It fits all Forest motorised track systems, like the FMS[®] system, FMS[®] Plus recess system, MRS[®] motorised rod system and also the DS[®]-XL motorised design system.

FOR USE IN

Hotels, offices, residences, boats and yachts, showrooms or anywhere a wireless motorised track system is required for curtains and drapes.

PRODUCT INFORMATION

- Li-ion rechargeable battery pack;
- Suitable for curtains up to 25 kg and 8 meter track length (straight track);
- Suitable for bended/curved curtain tracks with up to 2 bends in, for example, bay windows;
- A single full charge will last up to 6 months;
- Available colours: white, black.



FOREST SHUTTLE® Control Options

Our wide range of controls make finding a fit for your home even easier; controlling the curtains by hand, remote or even by building automation system. With the remote you can control the curtains in any position you like. When controlling the motorised curtain system by your smartphone or tablet, you can create and schedule customised room scenes that allow your curtains to operate on their own throughout the day.



FOREST DIAMOND SENSE REMOTE

15 or 2 Channel Remote control. Control up to 15 systems individually and in group by integrated timer function or manual. Auto-On mode, when holding hand above it, the integrated LED light will automatically come on. Radio control, range up to 30 meters. Including magnetic wall support.



FOREST WI-FI DONGLE

With the Shuttle[®] Wi-Fi dongle, you can control your motorised curtains on your mobile device via the Forest Connect app or even by voice command with the easy integration in for example Google Home, Amazon Echo or Apple Siri without the need for an additional hub or gateway.



FOREST WIRELESS CONNECTOR

The Forest Wireless Connector is an easy way to make the motorised curtain systems 'smart'. This wireless remote solution works in combination with an analogue timer or a smart plug such as services as Apple HomeKit or Google Assistant or Amazon Alexa become available. With the Forest Smart Plug it is possible to control by the Forest Connect app. The Wireless Connector is also easily incorporated into most popular building managent systems, including dry contact controls.




BUILDING AUTOMATION / HOTEL CONTROL

The Forest Shuttle® can be connected to any Building Automation system, by relay control.

SMART DEVICE CONNECTIVITY



Configure the right motorised curtain track system in a few steps.



3) Only with FIBARO Roller Shutter 3 / Walli Roller Shutter

4) In combination with an AC Control Set

FOREST SHUTTLE® WORKS WITH



* Only works with an actor.

Forest Shuttle® is compatible with many other Building Automation systems, thanks to its modular construction. A competitive advantage over other motorised drapery systems in the world!

FOREST SHUTTLE® Technical information



SHUTTLE[®] S

10 Years

Voltage Shuttle 24V DC 24V DC 100 - 240V~ 50 - 60Hz 0.8A **RF** Multi Receiver Internal Internal, optional Internal External, 100 - 240V AC -External, 100-240V AC -**Power Supply** Internal 0,8A - 50 - 60Hz; 1,5A - 50-60Hz; Output 24V DC - 2,5A Output 24V DC - 2,7A 65W 40W Max. power 40W Torque: 1.0 Nm 1.5 Nm 1.0 Nm 14-17cm/s 14-17 cm/s 14-17cm/s Speed: < 40 dB(A) Noise Level: $< 40 \, dB(A)$ < 40 dB(A) Max. curtain weight (without curves) 40 kg 70 kg 40 kg **Dimensions Motor:** 7 x 5 x 20 cm 7 x 5 x 25 cm 7 x 5 x 28 cm Net. Weight Motor 700 gr. 930 gr. 930 gr. **Dimensions Power Supply** 50 x 80 x 30 mm 50 x 110 x 30 mm IP20 IP20 IP20 Protection degree Max. running time 240 sec (in one direction) 240 sec (in one direction) 240 sec (in one direction) White / Anthracite / Black Colour options White / Grey / Anthracite / Black White / Anthracite / Grey / Black CE/FCC CE/FCC CE/FCC Certification & Marking: Touch Control technology $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ Integrated Emergency control $\sqrt{}$ V V **RF** Communication Standard V $\sqrt{}$ $\sqrt{}$ Z-Wave communication $\sqrt{}$ Automation System compatible $\sqrt{}$ $\sqrt{}$ Wi-Fi compatible $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ Works with DS-XL LED Dimmer $\sqrt{}$ $\sqrt{}$ (additional adaptor needed) Works with Wireless Connector $\sqrt{}$ $\sqrt{}$ 1 Can be used with curved track $\sqrt{}$ V Plug & Play $\sqrt{}$ $\sqrt{}$ $\sqrt{}$

10 Years

10 Years

SPECIFICATIONS

FEATURES

Warranty



SHUTTLE[®] AC

100 - 240V~ 50 - 60Hz 0.8A

100 - 240 V	50 - 00112 0.8
Internal	
Home Autor	mation 230V

	1014/
Max. power	40W
Torque:	1.0 Nm
Speed:	14-17cm/s
Noise Level:	< 41 dB(A)
Max. curtain weight (without curves)	40 kg
Dimensions Motor:	7 x 5 x 28 cm
Net. Weight Motor	980 gr.
Dimensions Power Supply	-
Protection degree	IP20
Max. running time	240 sec (in one direction)
Colour options	White
Certification & Marking:	CE
Touch Control technology	· 7
Integrated Emergency control	\checkmark
RF Communication Standard	\checkmark
Z-Wave communication	- / 7
Automation System compatible	\checkmark
Wi-Fi compatible	· / /
Works with DS-XL LED Dimmer	
Works with Wireless Connector	$\langle \cdot \rangle$
Can be used with curved track	\checkmark

SHUTTLE® iOn

14.8V DC
Internal
Charger Input 100 - 240~, 50-60Hz, 2.0A
Charger Output 16,8Vdc 1000mA
Removeable Battery Pack
30W
1.0 Nm
14-17cm/s
<40 dB(A)
25 kg
7 x 5 x 32,5 cm
1160 gr.
-
IP20
150 sec (in one direction)
White / Black
CE
\checkmark
\checkmark
\checkmark
- / /
\checkmark
- / /
(additional adaptor needed)
\checkmark
\checkmark
\checkmark
10 Years on motor, 2 years on battery pack

SPECIFICATIONS

Voltage Shuttle RF Multi Receiver

Power Supply

FEATURES

Plug & Play Warranty

10 Years

10 Years on motor, 2 years on battery pack

FOREST MOTORISED TRACK SYSTEM - FMS®



The Forest Shuttle[®] and the Forest motorised curtain track system (FMS[®]) make an unbeatable combination when it comes to noiseless operated curtains.

The FMS[®] System is an elegant system for all types of medium and heavyweight draperies. Available in one piece length of 7 metres. Can be extended up to 14 metres. Available in 5 colours: white, matt white, black, matt black or grey, making it suitable to fit in every design.

FMS[®] PLUS AND RECESS FIXATION

Instead of a regular ceiling fix or wall fix installation of the FMS[®] track system, Forest Group also offers a solution for recess fixed motorised curtain track. The FMS[®] Plus system is ideal for a clean, concealed curtain track installation. The recess profile can be fitted during the construction of the ceiling, the FMS[®] Plus motorised track can then be fitted once all the finishing works have been completed. The motor can be placed in a regular position, or upside down into the ceiling. The system can be fitted with the regular FMS[®] carriers, rotating carriers or the Forest Wave System for wave pleat.

FOR USE IN

Hotels, offices, residences, boats and yachts, showrooms, business meeting rooms, conference centers or anywhere a silent motorised track system is required for curtains and drapes.

PRODUCT INFORMATION

- Compact and noiseless operated motorised track system.
- All Shuttle[®] motors can be used on the FMS[®] System.
- Available in white, matt white, grey, black and matt black.
- Components in matching colours.
- Clickable off-set carriers for a straight heading of the curtain; roller bearing carriers and Easyflex carriers also available.
- Especially designed for use in combination with Forest Wave System.
- Motor can be mounted on the left or the right of the track.
- One-way draw or center (split) draw curtains possible.
- All KS[®] bracket compatible.
- Ceiling brackets and wall brackets available.
- FMS[®] track can be made in lengths of up to 14 meter.
- FMS[®] track can be curved / bent.
- Recess fixation possible by recess profile in combination with FMS[®] Plus track.
- Warranty: 10 years.



The FMS[®] Dual System is the new standard for the hotel industry when it comes to motorised curtain tracks. The FMS Dual is a unique motorised two channel curtain track system. Only one Shuttle motor is required to operate two channels. This system is designed to create an overlap that prevents light from entering the room. Thanks to the two channels, it is possible to adjust the overlap to any position. Ideal for hotels where guests arrive during the day after a long journey and want to rest first. The FMS[®] Dual ensures that the hotel room is completely darkened and no disturbing rays of light enter the room. The Dual system is easy to mount on the ceiling thanks to pre-drilled holes and additional carriers can easily be added later after the track has been fixed to the ceiling. In addition to single/double pleated curtains, the wave pleat can be applied via our FES[®] system.

BENDING / CURVING

The FMS[®] track and FMS[®] Plus track (except recess profile) can be bended and reversed bended with a radius of 20 cm (8"). Continuous curving can be bent and reverse bent with the Electric Powered Bender.



PROFILE

FMS® Track

- Weight 303 gr/mtr.
- Size 20 x 20 mm
- Aluminium extrusion
- Colours available: white, matt white, grey, black & matt black

FMS® Plus Track

- Weight 500 gr/mtr.
- Size 19,6 x 30 mm
- Aluminium extrusion
- Colours available:
 white, black & matt black

FMS® Plus Recess Profile

- Weight 555 gr/mtr.
- Size 26 x 32,20 mm
- Aluminium extrusion
- Colours available: white & matt black

FMS® Dual

- Weight 1,11 kg/mtr.
- Size 72 x 24 mm
- Aluminium extrusion
- Colour available: white & matt black




The FMS® track system is in four versions available:





20 mm





6

72 mm

3

FMS	FMS PLUS	FMS DUAL	MOTOR & CONTROL OPTIONS	ARTICLE	PACKING UNIT			ART.NR
•	•	•	Ĩ	SHUTTLE L Motor with internal RF Receiver, Touch Control and Emergency Control. 100 - 240V 50 - 60Hz 0.8A Power supply Dimensions 7 x 5 x 28 cm Up to 45 kg curtain weight	1/box	100-240V 100-240V 100-240V 100-240V 100-240V 100-240V 100-240V 100-240V 100-240V	white int. multi receiver white int. Z-Wave receiver white int. Z-Wave rec. ANZ white int. Z-Wave rec. India grey int. multi receiver anthracite int.multi receiver anthracite int. Z-Wave rec. EU black int. multi receiver black int. Z-Wave receiver EU	5232000001 5232000002 5232000007 5232000069 5232005001 5232005001 5232005002 5232006001 5232006002
•	•	•	N. F.	POWER CABLE FOR SHUTTLE L & S	1/box	EU 1.00 mtr EU 4.00 mtr UK 4.00 mtr USA 2.00 mtr AUS 1.80 mtr EU 4.00 mtr	white white white white white black	5201001101 5201001104 5201001134 5201001121 5201001141 5201006104
•	•	•		SHUTTLE M Strongest motor with internal RF Receiver, Touch Control System and Emergency Control. 24 V Power supply 100-240 V adaptor set to be ordered separately. Dimensions 7 x 5 x 25 cm Up to 75 kg curtain weight	1/box	24 Volt DC 24 Volt DC	white int. multi receiver white int. Z-Wave receiver EU white int. Z-Wave US/908Mhz grey int. multi receiver anthracite int. multi receiver black int. multi receiver black int. Z-Wave receiver EU	5232000003 5232000004 5232000006 5232003003 5232005003 5232006003 5232006004
				SHUTTLE M FOR SKYLIGHT SYSTEM (FSS) Motor with fixed drive	1/box	24 Volt DC	white int. multi receiver	7131000000
•	•	•		ADAPTOR SET SHUTTLE M Incl. cable and holder	1/box	EU 0.50 mtr EU 3.00 mtr UK 0.50 mtr USA 0.50 mtr EU 0.50 mtr	white white white white black	5201002002 5201002003 5201002004 5201002007 5201006002
•	•	•		SHUTTLE S Motor with internal RF Receiver, Touch Control and Emergency Control. 24 V Power supply 100-240 V adaptor set to be ordered separately. Dimensions 7 x 5 x 20 cm Up to 40 kg curtain weight	1/box	24 Volt DC	white int. multi receiver white int. Z-Wave receiver EU anthracite int. multi receiver anthracite Z-Wave receiver EU black int. multi receiver black int. Z-Wave receiver EU	5232000000 523200010 5232005000 5232005010 5232006000 5232006010
•	•	•		ADAPTOR SET SHUTTLE S Incl. holder / excl. cable	1/box	24 Volt	white	5232003002
•	•	•		SHUTTLE AC Motor with internal RF Receiverl and Emergency Control. Only for Building Management System. 100 - 240V 50 - 60Hz 0.8A Power supply Dimensions 7 x 5 x 28 cm Up to 40 kg curtain weight	1/box	100-240V	white	5233000000
•	•	•		SHUTTLE ION Incl. Battery Pack (14.4 V DC) Dimensions 7 x 5 x 32,5 cm Up to 25 kg curtain weight	1/box	Accu Pack	white black	5234000000 5234006000
•	•	•		SHUTTLE ION BATTERY PACK 4-Cell Lithium iOn Capacity 3400mAh	1/box		white black	5234000001 5234006001
•	•	•		SHUTTLE ION CHARGER CABLE 1.20 mtr cable	1/box	EU UK USA AUS	black black black black	5234000002 5234000003 5234000004 5234000005
•	•	•		DC EXTENSION CABLE FOR 24V ADAPTOR For use with Shuttle S/M adaptor and dimmer DS-XL LED	1/box	2 mtr	white	5209002200
				AC CONTROL SET Use the AC Control in combination with the Shuttle Motor for Live AC (Domotics) AC Control set complete	1/box	220 Volt	white grey black	5201002202 5201003202 5201006202
			U	Secondary unit-potential free relay		200V-240V	black white grey black	5201006202 5201002200 5201003200 5201006200
				Secondary unit-potential free relay		100V-120V	black white US	5201006200 5201002203

FMS	FMS PLUS	FMS DUAL	MOTOR & CONTROL OPTIONS & ACCESSORIES	ARTICLE	PACKING UNIT			ART.NR
•	•	•		Forest diamond sense remote control	1/box	Works with all Shuttle motors	white black	5201091470 5201096470
•	•	•		FOREST WIRELESS CONNECTOR Incl. 15 cm USB cable / excl USB charger One way transmitter to control curtains by third party Apps* (i.e. Google / Apple / Amazon) or by Domotics. *always in combination with Forest smart plug or third party plug	1/box	Works with all Shuttle motors	white	5201002270
•	•	•	F	FOREST WIRELESS CONNECTOR USB PLUG Use in combination with Forest Wireless Connector	1/box		EU UK AU US	5201002271-EU 5201002272-UK 5201002273-AU 5201002274-US
•	•	•		FOREST SMART PLUG WHITE The Forest Smart Plug allows App control via the Forest Connect App (the Forest Wireless Connector is required)	1/box	Works with all Shuttle motors	EU UK AU US	5201001952 5201001953 5201001954 5201001955
•	•	•		FOREST WIFI DONGLE Incl. cable WiFi 2.4GHz Power supply 12V DC 300mA max USB power 5V DC 1000mA max Control the curtains by Forest Connect App Easy integration third party apps by Google / Amazon Bi-directional	1/box	Works with all Shuttle motors except AC and iOn	white black	5201002280 5201006280
•	•	•	0	FOREST SHUTTLE TWILIGHT SENSOR (KAKU)	1/box	Works with all Shuttle motors (besides Shuttle iOn)	white	5201001951
•	•	•		FOREST WIRELESS WALL SWITCH 2-channel wall switch Dimensions: 8.5 x 8.5 x 1 cm	1/box	Works with all Shuttle motors	white black	5201001480 5201006480
•	•	•	T A	FOREST PULSE WALL SWITCH Can operate one motor only Dimensions: 6.5 x 5.5 x 2.7cm (2.56 x 2.17 x 1.06")	1/box		white	5201001900
•	•	•		SHUTTLE CLICK-ON RF MULTI RECEIVER For use with Forest remote in Z-Wave and building autmotion environments	1/box		white black	5201001362 5201006362
•	•			FOREST SHUTTLE DEMO FLIGHTCASE METAL Including: Shuttle L with FMS complete, FMS Plus Recess complete, FMS Dual Complete Samples: curved FMS, FMS (White, Grey and Black), MRS, DS-XL motorised, DS-XL LED Motorised, Remote Diamond Sense (White), Wireless Wall Switch (White), WiFi Dongle, Wireless Connector, Forest Smart Plug	Piece			9903000000
•	•	•		VELCRO HOTEL PROFILE Inside frame fix, to reduce light leakage in combination with looptape LOOPTAPE	120 mtr/ bundle 25 mtr/ roll			3581601600 3816202020

S	FMS PLUS	IS DUAL	FMS TRACK + COMPONENTS	ARTICLE	PACKING UNIT		ART.NR
FMS	FM	FMS I					
•			F	FMS TRACK 5.80 mtr (19') 7.00 mtr (23') 7.00 mtr (23') 7.00 mtr (23') 7.00 mtr (23') 7.00 mtr (23')	10/bundle	white white matt white grey black matt black	5101001580 5101001700 5101007700 5101003700 5101006700 5101008700
•				FMS CARRIER Klickable, offset, made of UV-resistant plastic. 10 Carriers on a breakaway strip, can be clicked into the the track after installation.	250/box	white grey black	2510101000 2510103000 2510106000
	•			ECONOMY SLIDE Can turn in the track	500/box	white black	2510601000 2510606000
•				FMS MASTER CARRIER SHORT R/L WHITE For use with single pleat or pinch pleat curtains For use with one way draw curtains To use in combination with Wave Return Pulley	25/box	white black	5215801001 5215806001
•				FMS MASTER CARRIER UNDERLAP CLICK ON Reversible Usable for Click on stiffner	15/box	white matt white grey black matt black	5215801010 5215801010-M 5215803010 5215806010 5215806010-M
•				FMS MASTER CARRIER OVERLAP CLICK ON Reversible Usable for Click on stiffner	15/box	white matt white grey black matt black	5215901010 5215901010-M 5215903010 5215906010 5215906010-M
•			اللہ اللہ اللہ اللہ اللہ اللہ اللہ اللہ	FMS MASTER CARRIER UNDERLAP SINGLE LONG R/L Reversible For single draw curtains	15/box	white black matt black	3016001000 3016006000 3016006000-M
•			1.2 2 2 2 2 2 2 2	PROLONGED OVERLAP CLICK ON 150 mm long 200 mm long	15/box	white matt white black matt black	9500001010 9500001010-M 9500006010 9500006010-M
•				Z-SHAPED OVERLAP ARM Reversible Z-shaped overlap arm. Fits FMS master carriers. For further reducing of light leakage for center closing.	15/box	white	9500001020 9500001030
•				STIFFENER CLICK-ON Recommended to attach to the FMS master carri- ers, stiffner to be stitched into the curtain	15/box		5116001001
•			taaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa	FMS TRANSPORT BELT Toothed belt, to be installed inside the FMS Track	100mtr/roll		5105501000
•				FMS CONNECTOR To fix the FMS Master Carrier onto the FMS transport belt	50/box	white grey black	5103011500 5103013500 5103016500
•				FMS MOTOR PULLEY Connects motor with FMS Track	1/box	white grey black	5103011000 5103013000 5103016000
				FMS MOTOR PULLEY UPSIDE DOWN	1/box 1/box	white	5103011003
•				45 degrees adjustable Only for up to 7kg curtain weight (Shuttle M)			
•				FMS RETURN PULLEY Reverses the FMS transport belt in the FMS track For center draw curtains	1/box	white grey black	5103011100 5103013100 5103016100
•			···	FMS TRACK JOINER Used to make a solid connection between two pieces of track	10/box	white grey black	2518401000-A 2518403000 2518406000

FMS	FMS PLUS	FMS DUAL	WAVE COMPONENTS FOR FMS	ARTICLE	PACKING UNIT		ART.NR
•			And	WAVE ADJUSTABLE MASTER CARRIER UNDERLAP For use with wave pleat curtains (Easyflex) See additional components below	25/box	white black	4813001050 4813006050
•				WAVE BELT CONNECTOR CENTER DRAW For use with wave pleat curtains (Easyflex) To use in combination with adjustable wave carrier	50/box	white black	4813001040 4813006040
•				WAVE BELT CONNECTOR ONE-WAY DRAW For use with wave pleat curtains (Easyflex) To use in combination with adjustable wave carrier	50/box	white black	4813001030 4813006030
•				WAVE RETURN PULLEY MOTORISED For use with wave pleat, single or pinch pleat curtains For wave pleat curtains use in combination with adjus- table wave carrier (Easyflex) For single/pinch pleat curtains use in combination with FMS Master carrier short R/L White	25/box	white black	4813001060 4813006060
•			$\overline{\mathbf{O}}$	WAVE DS-XL END STOP To use in combination with adjustable wave carrier Easyflex For center draw curtains	100/box		3916001000
•				FMS RETURN PULLEY EASYFLEX For use with wave pleat curtains (Easyflex) For single draw curtains	1/box	white grey black	5103011102 5103013102 5103016102
•				WAVE ADJUSTABLE HOOK MOTOR For use with wave pleat curtains (Easyflex)	25/box	white black	4813001010 4813006010
•				WAVE ADJUSTABLE HOOK RETURN PULLEY For use with wave pleat curtains (Easyflex)	25/box	white black	4813001020 4813006020
•				EASYFLEX MASTER CARRIER LEFT For use with wave pleat curtains (Easyflex) For center draw 90 degrees left for small stiffener	25/box	white grey black white	4815351090 4815353090 4815356090 4815361090
•				EASYFLEX MASTER CARRIER RIGHT For use with wave pleat curtains (Easyflex) Center draw 90 degrees right for small stiffener	25/box	white grey black	4815451090 4815453090 4815456090 4815461090
•				EASYSNAP MASTER CARRIER LEFT For use with wave pleat curtains (Easysnap) 90 degrees	15/box	white	4815301090
•				EASYSNAP MASTER CARRIER RIGHT For use with wave pleat curtains (Easysnap) 90 degrees	15/box	white	4815401090
•				EASYSNAP FMS MASTER CARRIER For use with wave pleat curtains (Easysnap)	15/box	white	4815401000
•				EASYSNAP FMS UNDERLAP L/R For use with wave pleat curtains (Easysnap)	15/box	white	4815401000
•				WAVE STIFFENER CLICK ON 'SMALL' For use with wave pleat curtains (Easyflex/Easysnap) Recommended to attach to the FMS master carriers, stiffner to be stitched into the curtain	15/box	white	4815001001

	FMS PLUS	FMS DUAL	FMS PLUS TRACK + COMPONENTS	ARTICLE	PACKING UNIT		ART.NR
FMS	FMS	FMS					
				FMS PLUS TRACK 7.00 mtr (23')	10/bundle	white black	5131001700 5131006700
	•			5,80 mtr (19')	10/bundle	matt black	5131006580-MAT
	•			FMS PLUS RECESS PROFILE 7.00 mtr (23')	1/piece	white matt black	5131011100 5131016700-MAT
	•			FMS PLUS RECESS PROFILE FIXING STRIP 7.00 mtr (23') length	1 piece	white black	5131001600 5131006600
	•			FMS PLUS RECESS FIXING WEDGE To fix the track into the recess profile	10/box	white black	5131001100 5131006100
	•			FMS PLUS RECESS CORNER TRACK Preshaped 90 degrees curve for FMS PLUS track	1/piece	white	5131011790
	•		H	ECONOMY CARRIER Can turn in the track	100/box	white black	2510601000 2510606000
	•		0.03 (1)	FMS PLUS MASTER CARRIER UNDERLAP Arm is reversible, incl. belt connector For use with wave pleat curtains in combination with FES-system (Easyflex)	10/box	white black	5135801000 5135806000
	•		510 ° C	FMS PLUS MASTER CARRIER OVERLAP Arm is reversible, incl. belt connector For use with wave pleat curtains in combination with FES-system (Easyflex)	10/box	white matt black	5135901000 5135906000-M
	•			FMS PLUS MASTER CARRIER EASYFLEX L&R 90 degrees For use with wave pleat curtains in combination with FES-system (Easyflex)	10/box	white	5135901010
	•			FMS PLUS TRANSPORT BELT Toothed belt to be installed inside FMS Plus track 9.3 x 2.2mm Material: KEVLAR	100mtr/roll		5135501001
	•			FMS PLUS MOTOR PULLEY Reverse the FMS PLUS belt in the FMS PLUS track	5/box	white black	5133011000 5133016000
	•			FMS PLUS RETURN PULLEY Reverse the FMS PLUS belt in the FMS PLUS track	5/box	white black	5133011100 5133016100
	•			FMS PLUS MOTOR PULLEY UPSIDE DOWN Can be used to place the motor upside down (recess)	1/box	white	5133011003

FMS	FMS PLUS	FMS DUAL	FMS PLUS TRACK + COMPONENTS	ARTICLE	PACKING UNIT		ART.NR
	•			FMS PLUS L-PULLEY To create a double overlapping track system in combi- nation with only one motor	1/box	white	5133011101
	•			FMS PLUS RECESS COVER PLATE	1/box	white black	5133011104 5133016104
	•			FMS PLUS RECESS COVER PLATE UPSIDE DOWN Cover plate for recess; motor pulley	1/box	white black	5133011004 5133016004
	•			CRS DECO / MRS / FMS PLUS TRACK CONNECTOR Suitable for fms plus with recess profile	25/box		5815200005
	•		() ()	FMS PLUS BRIDGE 6,5 cm 28 cm	10/box	white black white black	4518701000 4518706000 4518601000 4518606000
	•			FMS PLUS TRACK CONNECTOR PIN Stainless steel, 2 x 20mm For a firm seamless connection	50/box		990000012

FMS	FMS PLUS	FMS DUAL	FMS DUAL TRACK + COMPONENTS	ARTICLE	PACKING UNIT		ART. NR
		•		FMS DUAL Two glide track predrilled, aluminium extrusion, white powder coated, lubricated	1 length/7 mtr	white matt black	3851001700 3851006700-MAT
		•		FMS DUAL UPPER TRACK CONNECTOR Used to make a solid connection between two pieces of track	10/box	aluminium	3851000003
		•		FMS DUAL LOWER TRACK CONNECTOR For optimal guiding of the transport belt between two pieces of track	25/box	white black	3851000002 3851006002
		•		FMS DUAL MOTOR PULLEY Connects motor with track	5/box	white black	3851000004 3851006004
		•		FMS DUAL RETURN PULLEY Reverses the transport belt in the track	10/box	white black	3851000005 3851060005
		•		FMS DUAL ENDSTOP Plastic end stop can be used to set the overlap position	25/box	white black	3851000006 3851006006
		•		FMS DUAL MASTER SET For positioning the 1st carrier	10/box	white black	3851000007 3851006007
		•		FMS DUAL TRANSPORT BELT Toothed belt, to be installed inside the track	100 mtr/roll		3851000001
		•		MCS COVER CAP, 10mm. The cap covers the screw hole and ensures a stylish and ultimate finished look.	500/box	white black	5399999999 5399999996
		•	Ĩ	KS ASYMMETRICAL CARRIER	500/box	white black	1010001000 1010006000

FMS	FMS PLUS	FMS DUAL	MOUNTING OPTIONS + OTHER ITEMS	ARTICLE	PACKING UNIT		ART. NR
•	•			SMART KLICK CEILING BRACKET Incl. cover cap 'Klicks' onto track, powder coated	100/box	white grey black	1018201001 1018203001 1018206001
				ALUMINIUM WALL BRACKET 7.5 cm single (3')	20/box	white grey black	1020301075 1020303075 1020306075
				ALUMINIUM WALL BRACKET 10 cm single (4') ALUMINIUM WALL BRACKET	20/box 15/box	white grey black white	1020301100 1020303100 1020306100 1020301150
•	•			15 cm double (6') ALUMINIUM WALL BRACKET	15/box	grey black white	1020303150 1020306150 1020301200
			Ø	20 cm double (8') ALUMINIUM WALL BRACKET 25 cm triple (10')	15/box	grey black white grey black	1020303200 1020306200 1020301250 1020303250 1020306250
•	•		Ē	SMART KLICK COVER CAP ALU WALL BRACKET UNIVERSAL	50/box	white grey black	1021301000 1021303000 1021306000
•	•			FSS MOUNTING BRACKET For concealed installation or ceiling installation in narrow spaces. Heavy Duty.	100/box		7160001000
	10		BENDING				
FMS	FMS PLUS	FMS DUAL	COMPONENTS + OTHER ITEMS	ARTICLE	PACKING UNIT		ART. NR
•	•			CONTRACT BENDING TOOL BASIC for FMS and FMS Plus	1/each		256000000
			$(\hat{\bullet})$	FMS CONTRACT BENDING WHEEL radius 20 cm incl. wedges	1/each		2561000000
				FMS PLUS CONTRACT BENDING WHEEL ALL-IN radius 20 cm incl. wedges and bending strips	1/each		5131000000
•				FMS BENDING STRIPS 90 cm T-bending strip	1/each		5160100000
	•			FMS PLUS SET BENDING STRIPS 90 cm	1/each		5131000001
				BENDING STAND Stand for contract bending tool	1/each		2560800000
•	•			ELECTRIC POWERED BENDER	1/each	230V 110V	1060500000 1060500001
•				FMS BENDING WHEEL for electric bender, set of 3	1/set		2560700000
				FMS PLUS BENDING WHEEL for electric bender, set of 3	1/set		
•				FMS/CS BENDING STRIP for electric bender 700 cm	1/each		5160100010
	•			FMS PLUS BENDING STRIPS for electric bender	1/piece		5160800000
•	•	•		FOREST LUBRICANT To lubricate components during assembly	1/box		5109010000



0**f** in 🖰