

# FOREST SHUTTLE® & FMS® Series

The Forest Shuttle® curtain motor and the Forest Motorised curtain track System (FMS®) make an unbeatable combination when it comes to a troublefree operated electric curtains.



### FOREST SHUTTLE® Series



When it comes to comfort, the Forest Shuttle® lives up to its expectations. Being able to open and close your curtains remotely, from the comfort of your chair, when you are on holiday, automatically at pre-programmed opening and closing times or even linked to variable sunrise and sunset times. The Forest Shuttle® is the silent force behind the opening and closing of curtains all over the world.

The Shuttle® can be fully integrated in all major home automation systems.

For maximum safety, integrated emergency control ensures manual operation of the drapery in case of power failure.

The smooth and silent running curtain track system can, in addition to remote operation, also be operated by hand. Thanks to Touch Control technology, a gentle pull on the curtain is enough to activate the motor.

### **COLOUR OPTIONS SHUTTLE®**









White

Grey

ey Anthracite

Black

### PRODUCT INFORMATION

The Forest Shuttle® family of motors offer the following functions:

- High quality, extremely reliable and ultra silent motor.
- Integrated RF multi receiver, for Diamond Sense Remote control or wall switch.
- Various control options: App control, Remote Control (RF), Wall Switch Domotics, Building/Hotel Automation, Serial Communication, Z-Wave etc.
- Full automatic setting of the limits.
- Programming of intermediate positions possible.
- Touch Control Technology, gently pulling the curtain by hand will activate the motor. Sensitivity adjustable (except for the Shuttle® AC).
- Integrated Emergency Control with automatic declutch in case of power failure, to ensure a manual operation of the curtains.
- Stack-back position programmable to every desired setting;
- Can be used in combination with various motorised track systems like FMS System (standard option), FMS Dual Channel system, Motorised Design System (DS-XL LED) and Motorised Rod System (MRS).
- Can be mounted on the left or the right side of the track.
- Can be used with curved Forest motorised track systems.
- Integrated Z-Wave Plus as option (only Shuttle® S/M/L).
- For Skylight System (FSS®) a special Shuttle® M motor with receiver and fixed drive is available.
- Tandem motor application possible as well.
- Upside down inverted motor mounting available.
- Variable velocity with slow start and slow stop.
- Warranty: 10 years on motor (2 years on battery pack iOn)



### **DECORATIVE TRACK OPTIONS**

The whole range of Forest motors' are totally compatible throughout our electrically operated curtain track range including the decorative options like the DS-XL® LED motorised system and the Motorised Rod System (MRS®).





DS-XL® LED DESIGN TRACK



MRS® MOTORISED ROD TRACK

### **SMART HOME DEMO SUITCASE**

We have redesigned our demo case for motorised systems. Besides samples of our standard motorised curtain track system, FMS®, and the FMS® Plus with recess profile, you will also find the new two-channel system, FMS® Dual, and our motorised rod system, MRS®. Easily demonstrate app operation thanks to the included WiFi dongle and the Wireless Connector. All other operating modes, accessories and documentation are of course included.



### **FOREST SHUTTLE® SERIES**

The Forest Shuttle® is offered in 5 versions. Choose which Forest Shuttle motor best suits your application integration needs:



# FOREST SHUTTLE® iOn



Our bestselling Forest Shuttle® system is also available in a wireless, battery powered version. The Shuttle® iOn is perfect for areas without nearby power points.

An extensive period of research, development and endurance testing on countless of track set-ups has resulted in the Forest Shuttle® iOn. The Shuttle® iOn's motor is fitted with an internal, removable heavy duty battery pack. Depending on the track size and curtain weight, the battery only needs to be charged 2 to 3 times per year.

You can expect the same unique functionalities as that of the wired Shuttle® L, like Touch Control technology. The motor has an integrated Multi RF receiver, allowing for operation using any Forest remote control option.

### Unique in the market

The Shuttle® iOn can be used in combination with curved tracks (max. 2 bends), which is unique in the market. It fits all Forest motorised track systems, like the FMS® system, FMS® Plus recess system, MRS® motorised rod system and also the DS®-XL motorised design system.

### **FOR USE IN**

Hotels, offices, residences, boats and yachts, showrooms or anywhere a wireless motorised track system is required for curtains and drapes.

### PRODUCT INFORMATION

- Li-ion rechargeable battery pack;
- Suitable for curtains up to 25 kg and 8 meter track length (straight track);
- Suitable for bent/curved curtain tracks with up to 2 bends in, for example, bay windows;
- A single full charge will last up to 6 months;
- Available colours: white, black.



# FOREST SHUTTLE® Control Options

Our wide range of controls make finding a fit for your home even easier; controlling the curtains by hand, remote or even by building automation system. With the remote you can control the curtains in any position you like. When controlling the motorised curtain system by your smartphone or tablet, you can create and schedule customised room scenes that allow your curtains to operate on their own throughout the day.



### **FOREST DIAMOND** SENSE REMOTE

15 or 2 Channel Remote control. Control up to 15 systems individually and in group by integrated timer function or manual. Auto-On mode, when holding hand above it, the integrated LED light will automatically come on. Radio control, range up to 30 meters. Including magnetic wall support.



### **FOREST WI-FI DONGLE**

With the Shuttle® Wi-Fi dongle, you can control your motorised curtains on your mobile device via the Forest Connect app or even by voice command with the easy integration in for example Google Home, Amazon Echo or Apple Siri without the need for an additional hub or gateway.



### **FOREST WIRELESS** CONNECTOR

The Forest Wireless Connector is an easy way to make the motorised curtain systems 'smart'. This wireless remote solution works in combination with an timer or smart plug with services such as Apple HomeKit or Google Assistant or Amazon Alexa become available. With the Forest Smart Plug it is possible to control by the Forest Connect app. The Wireless Connector is also easily incorporated into most popular building managent systems, including dry contact controls.



### BUILDING AUTOMATION / HOTEL CONTROL

The Forest Shuttle® can be connected to any Building Automation system, by relay control.

### **SMART DEVICE** CONNECTIVITY



Configure the right motorised curtain track system in a few steps.

| EL PERSONAL   |               |                           |             |            |                    |             |               |              | Voice<br>ontro   |            |
|---|---------------|---------------------------|-------------|------------|--------------------|-------------|---------------|--------------|------------------|------------|
|   | Shuttle S/M/L | Shuttle S/M/L with Z-Wave | Shuttle iOn | Shuttle AC | Forest Connect app | Google Home | Apple Homekit | Amazon Alexa | Google Assistant | Apple Siri |
| Forest Wireless Connector<br>One way transmitter to control<br>curtains by third party apps or by<br>Domotics. (433Mhz) | •             |                           | •           |            | •1                 | •1          | •2            | •1           | •1               | •1         |
| Forest Wi-Fi Dongle in combination with Forest Connect app  | •             | •                         |             |            | •                  | •           |               | •            | •                | •          |
| Smartwares Controller<br>in combination with<br>HomeWizard lite app (433 Mhz)   | •             |                           | •           |            |                    |             |               | •            |                  |            |
| Homey in combination with<br>Homey app  | •             | •                         | •           |            |                    | •           | •             | •            | •                | •          |
| FIBARO System in combination with FIBARO Home Center app  |               | •                         |             | •3         |                    | •           | •             | •            | •                | •          |
| Samsung SmartThings Hub in<br>combination with Samsung<br>SmartThings app   |               | •                         |             |            |                    | •           | •             | •            | •                | •          |
| 230 Volt hard-wired building<br>management system   | •4            |                           |             | •          |                    |             |               |              |                  |            |
| 1) In combination with Forest sma   | rt plug       |                           |             |            |                    |             |               |              | '                |            |

- 3) In combination with Apple Homekit smart plug
  3) Only with FIBARO Roller Shutter 3 / Walli Roller Shutter
  4) In combination with an AC Control Set

### **FOREST SHUTTLE® WORKS WITH**







CRESTRON.

Control (4)





\* Only works with an actor.

Forest Shuttle® is compatible with many other Building Automation systems, thanks to its modular construction. A competitive advantage over other motorised drapery systems in the world!

# FOREST SHUTTLE® Technical information



| 2        |
|----------|
| 0        |
| Ĕ        |
| J        |
| 핕        |
|          |
| <b>P</b> |
| • 1      |

Automation System compatible

Works with DS-XL LED Dimmer

Works with Wireless Connector Can be used with curved track

10 Years

Wi-Fi compatible

Plug & Play Warranty

|                                      | SHUTTLE" S                 | SHUTTLE" M                        | SHUTTLE" L                        |
|--------------------------------------|----------------------------|-----------------------------------|-----------------------------------|
|                                      |                            |                                   |                                   |
| Voltage Shuttle                      | 24V DC                     | 24V DC                            | 100 - 240V~ 50 - 60Hz 0.8A        |
| RF Multi Receiver                    | Internal                   | Internal, optional                | Internal                          |
| Power Supply                         | External, 100 - 240V AC -  | External, 100-240V AC -           | Internal                          |
|                                      | 0,8A - 50 - 60Hz;          | 1,5A - 50-60Hz;                   |                                   |
|                                      | Output 24V DC - 2,5A       | Output 24V DC - 2,7A              |                                   |
| Max. power                           | 40W                        | 65W                               | 40W                               |
| Torque:                              | 1.0 Nm                     | 1.5 Nm                            | 1.0 Nm                            |
| Speed:                               | 14-17cm/s                  | 14-17 cm/s                        | 14-17cm/s                         |
| Noise Level:                         | < 40 dB(A)                 | < 40 dB(A)                        | < 40 dB(A)                        |
| Max. curtain weight (without curves) | 40 kg                      | 70 kg                             | 40 kg                             |
| Dimensions Motor:                    | 7 x 5 x 20 cm              | 7 x 5 x 25 cm                     | 7 x 5 x 28 cm                     |
| Net. Weight Motor                    | 700 gr.                    | 930 gr.                           | 930 gr.                           |
| Dimensions Power Supply              | 50 x 80 x 30 mm            | 50 x 110 x 30 mm                  | -                                 |
| Protection degree                    | IP20                       | IP20                              | IP20                              |
| Max. running time                    | 240 sec (in one direction) | 240 sec (in one direction)        | 240 sec (in one direction)        |
| Colour options                       | White / Anthracite / Black | White / Grey / Anthracite / Black | White / Anthracite / Grey / Black |
| Certification & Marking:             | CE/FCC                     | CE/FCC                            | CE/FCC                            |
|                                      |                            |                                   |                                   |
| Touch Control technology             | $\sqrt{}$                  | V                                 | $\checkmark$                      |
| Integrated Emergency control         | $\checkmark$               | V                                 | $\checkmark$                      |
| RF Communication Standard            | √                          | $\checkmark$                      | $\checkmark$                      |
| Z-Wave communication                 | V                          | $\checkmark$                      | $\checkmark$                      |
|                                      |                            |                                   |                                   |

10 Years

√ (additional adaptor needed)

10 Years



# **SPECIFICATIONS**

| Voltage Shuttle   |  |
|-------------------|--|
| RF Multi Receiver |  |
| Power Supply      |  |
|                   |  |

| Max. power                           |
|--------------------------------------|
| Torque:                              |
| Speed:                               |
| Noise Level:                         |
| Max. curtain weight (without curves) |
| Dimensions Motor:                    |
| Net. Weight Motor                    |
| Dimensions Power Supply              |
| Protection degree                    |
| Max. running time                    |
| Colour options                       |

# **FEATURES**

| ivet. vveignt motor           | 200 gi.  |
|-------------------------------|--|
| Dimensions Power Supply       | -  |
| Protection degree             | IP20   |
| Max. running time             | 240 sec (in one direction)                       |
| Colour options                | White  |
| Certification & Marking:      | CE   |
|                               |  |
| Touch Control technology      | -  |
| Integrated Emergency control  | $\checkmark$                                     |
| RF Communication Standard     | $\checkmark$                                     |
| Z-Wave communication          | - / /  |
| Automation System compatible  | <b>√</b> /                                       |
| Wi-Fi compatible              | - //   |
| Works with DS-XL LED Dimmer   | <del>/</del> /////////////////////////////////// |
| Works with Wireless Connector | (- /   |
| Can be used with curved track | $\checkmark$                                     |
| Plug & Play                   | /-   |
| Warranty                      | 10 Years   |
|                               |  |

| 400 2401/2 50 6011-0.04                | 44.077.00                               |
|--|---|
| 100 - 240V <sup>∼</sup> 50 - 60Hz 0.8A | 14.8V DC                                |
| Internal                               | Internal                                |
| Home Automation 230V                   | Charger Input 100 - 240~, 50-60Hz, 2.0A |
|  | Charger Output 16,8Vdc 1000mA           |
|  | Removeable Battery Pack                 |
| 40W                                    | 30W                                     |
| 1.0 Nm                                 | 1.0 Nm                                  |
| 14-17cm/s                              | 14-17cm/s                               |
| < 41 dB(A)                             | <40 dB(A)                               |
| 40 kg                                  | 25 kg                                   |
| 7 x 5 x 28 cm                          | 7 x 5 x 32,5 cm                         |
| 980 gr.                                | 1160 gr.                                |
| -                                      | -                                       |
| IP20                                   | IP20                                    |
| 240 sec (in one direction)             | 150 sec (in one direction)              |
| White                                  | White / Black                           |
| CE                                     | CE                                      |
|  |   |
|  | $\checkmark$                            |
| $\checkmark$                           | $\checkmark$                            |
| <b>√</b>                               | $\checkmark$                            |
| - / / / /                              | - / /                                   |
| <b>√</b>                               | √                                       |
| - /                                    | - / /                                   |

 $\sqrt{}$  (additional adaptor needed)

10 Years on motor, 2 years on battery pack

# **FOREST MOTORISED TRACK SYSTEM - FMS®**



The Forest Shuttle® and the Forest motorised curtain track system (FMS®) make an unbeatable combination when it comes to noiseless operated curtains.

The FMS® System is an elegant system for all types of medium and heavyweight draperies. Available in one piece length of 7 metres. Can be extended up to 14 metres. Available in 5 colours: white, matt white, black, matt black or grey, making it suitable to fit in every design.

# FMS® PLUS AND RECESS FIXATION

Instead of a regular ceiling fix or wall fix installation of the FMS® track system, we also offer a solution for a recess fixed motorised curtain track. The FMS® Plus system is ideal for a clean, concealed curtain track installation. The FMS® Plus track and recessed profile are installed after the ceiling has been plastered and finalised. Because the recess profile is coated, the stucco does not adhere to the profile, which can cause cracks. Therefore, we strongly recommend installing the recess profile over the stucco. The motor can be placed in a regular position, or upside down into the ceiling. The system can be fitted with the regular FMS® carriers, rotating carriers or the Forest Wave System for wave pleat.

### **FOR USE IN**

Hotels, offices, residences, boats and yachts, showrooms, business meeting rooms, conference centers or anywhere a silent motorised track system is required for curtains and drapes.

### **PRODUCT INFORMATION**

- Compact and noiseless operated motorised track system.
- All Shuttle® motors can be used on the FMS® System.
- Available in white, matt white, grey, black and matt black.
- Components in matching colours.
- Clickable off-set carriers for a straight heading of the curtain; roller bearing carriers and Easyflex carriers also available.
- Especially designed for use in combination with Forest Wave System.
- Motor can be mounted on the left or the right of the track.
- One-way draw or center (split) draw curtains possible.
- All KS<sup>®</sup> bracket compatible.
- Ceiling brackets and wall brackets available.
- FMS® track can be made in lengths of up to 14 meter.
- FMS® track can be curved / bent.
- Recess fixation possible by recess profile in combination with FMS® Plus track.
- Warranty: 10 years.

### FMS® DUAL NEW!

The FMS® Dual System is the new standard for the hotel industry when it comes to motorised curtain tracks. The FMS Dual is a unique motorised two channel curtain track system. Only one Shuttle motor is required to operate two channels. This system is designed to create an overlap that prevents light from entering the room. Thanks to the two channels, it is possible to adjust the overlap to any position. Ideal for hotels where guests arrive during the day after a long journey and want to rest first. The FMS® Dual ensures that the hotel room is completely darkened and no

disturbing rays of light enter the room. The Dual system is easy to mount on the ceiling thanks to pre-drilled holes and additional carriers can easily be added later after the track has been fixed to the ceiling. In addition to single/double pleated curtains, the wave pleat can be applied via our FES® system.

### **BENDING / CURVING**

The FMS® track and FMS® Plus track (except recess profile) can be bent and reversed bent with a radius of 20 cm (8"). Continuous curving can be bent and reverse bent with the Electric Powered Bender.



### **PROFILE**

### FMS® Track

- Weight 303 gr/mtr.
- Size 20 x 20 mm
- Aluminium extrusion
- Colours available: white, matt white, grey, black & matt black

### FMS® Plus Track

- Weight 500 gr/mtr.
- Size 19,6 x 30 mm
- Aluminium extrusion
- Colours available: white, black & matt black

### FMS® Plus Recess Profile


- Weight 555 gr/mtr.
- Size 26 x 32,20 mm
- Aluminium extrusion
- Colours available: white & matt black


### FMS® Dual

- Weight 1,11 kg/mtr.
- Size 72 x 24 mm
- Aluminium extrusion
- Colour available: white & matt black









### **FOREST FMS® TRACKS**

The FMS® track system is in four versions available:













**RECESS PROFILE** WITH FMS® **PLUS TRACK** 













G = Gloss

M = Matt

- 1 Shuttle® Motor
- (2) Motor Pulley
- (3) FMS® Track
- (4) FMS® Return Pulley
- (5) FMS® Glider
- (6) FMS® Master Carrier Underlap
- (7) FMS® Master Carrier Overlap
- (8) Stiffener Small



| FMS | FMS PLUS | FMS DUAL | MOTOR & CONTROL OPTIONS | ARTICLE  | PACKING<br>UNIT |  |   | ART.NR  |
|-----|----------|----------|-------------------------|--|-----------------|--|---|---|
| •   | •        | •        |                         | SHUTTLE L Motor with internal RF Receiver, Touch Control and Emergency Control. 100 - 240V 50 - 60Hz 0.8A Power supply Dimensions 7 x 5 x 28 cm Up to 45 kg curtain weight   | 1/box           | 100-240V<br>100-240V<br>100-240V<br>100-240V<br>100-240V<br>100-240V<br>100-240V<br>100-240V<br>100-240V | white int. multi receiver white int. Z-Wave receiver white int. Z-Wave rec. ANZ white int. Z-Wave rec. India grey int. multi receiver anthracite int. multi receiver anthracite int. Z-Wave rec. EU black int. multi receiver black int. Z-Wave receiver EU | 5232000001<br>5232000002<br>5232000007<br>52320000069<br>5232003001<br>5232005001<br>5232005002<br>5232006001<br>5232006002 |
| •   | •        | •        |                         | POWER CABLE FOR SHUTTLE L & S  | 1/box           | EU 1.00 mtr<br>EU 4.00 mtr<br>UK 4.00 mtr<br>USA 2.00 mtr<br>AUS 1.80 mtr<br>EU 4.00 mtr                 | white white white white white white black   | 5201001101<br>5201001104<br>5201001134<br>5201001121<br>5201001141<br>5201006104  |
| •   | •        | •        |                         | SHUTTLE M Strongest motor with internal RF Receiver, Touch Control System and Emergency Control. 24 V Power supply 100-240 V adaptor set to be ordered separately. Dimensions $7 \times 5 \times 25$ cm Up to 75 kg curtain weight | 1/box           | 24 Volt DC<br>24 Volt DC<br>24 Volt DC<br>24 Volt DC<br>24 Volt DC<br>24 Volt DC<br>24 Volt DC           | white int. multi receiver white int. Z-Wave receiver EU white int. Z-Wave US/908Mhz grey int. multi reciever anthracite int. multi receiver black int. multi receiver black int. Z-Wave receiver EU   | 5232000003<br>5232000004<br>5232000006<br>5232003003<br>5232005003<br>5232006003<br>5232006004                              |
|     |          |          |                         | SHUTTLE M FOR SKYLIGHT SYSTEM (FSS)<br>Motor with fixed drive  | 1/box           | 24 Volt DC   | white int. multi receiver   | 7131000000  |
| •   | •        | •        |                         | ADAPTOR SET SHUTTLE M<br>Incl. cable and holder  | 1/box           | EU 0.50 mtr<br>EU 3.00 mtr<br>UK 0.50 mtr<br>USA 0.50 mtr<br>EU 0.50 mtr                                 | white<br>white<br>white<br>white<br>black   | 5201002002<br>5201002003<br>5201002004<br>5201002007<br>5201006002  |
| •   | •        | •        |                         | SHUTTLE S Motor with internal RF Receiver, Touch Control and Emergency Control. 24 V Power supply 100-240 V adaptor set to be ordered separately. Dimensions 7 x 5 x 20 cm Up to 40 kg curtain weight                              | 1/box           | 24 Volt DC   | white int. multi receiver<br>white int. Z-Wave receiver EU<br>anthracite int. multi receiver<br>anthracite Z-Wave receiver EU<br>black int. multi receiver<br>black int. Z-Wave receiver EU   | 5232000000<br>5232000010<br>5232005000<br>5232005010<br>5232006000<br>5232006010  |
| •   | •        | •        |                         | ADAPTOR SET SHUTTLE S<br>Incl. holder / excl. cable  | 1/box           | 24 Volt  | white   | 5232003002  |
| •   | •        | •        |                         | SHUTTLE AC Motor with internal RF Receiverl and Emergency Control. Only for Building Management System. 100 - 240V 50 - 60Hz 0.8A Power supply Dimensions 7 x 5 x 28 cm Up to 40 kg curtain weight                                 | 1/box           | 100-240V   | white   | 5233000000  |
| •   | •        | •        |                         | SHUTTLE ION Incl. Battery Pack (14.4 V DC) Dimensions 7 x 5 x 32,5 cm Up to 25 kg curtain weight   | 1/box           | Accu Pack  | white<br>black  | 5234000000<br>5234006000  |
| •   | •        | •        |                         | SHUTTLE ION BATTERY PACK<br>4-Cell Lithium iOn<br>Capacity 3400mAh   | 1/box           |  | white<br>black  | 5234000001<br>5234006001  |
| •   | •        | •        |                         | SHUTTLE ION CHARGER CABLE<br>1.20 mtr cable  | 1/box           | EU<br>UK<br>USA<br>AUS   | black<br>black<br>black<br>black  | 5234000002<br>5234000003<br>5234000004<br>5234000005  |
| •   | •        | •        |                         | DC EXTENSION CABLE FOR 24V ADAPTOR<br>For use with Shuttle S/M adaptor and dimmer<br>DS-XL LED   | 1/box           | 2 mtr  | white   | 5209002200  |
|     |          |          |                         | AC CONTROL SET Use the AC Control in combination with the Shuttle Motor for Live AC (Domotics) AC Control set complete   | 1/box           | 220 Volt   | white<br>grey   | 5201002202<br>5201003202  |
|     |          |          |                         | Secondary unit-potential free relay  |                 | 200V-240V  | black<br>white<br>grey  | 5201006202<br>5201002200<br>5201003200  |
|     |          |          |                         | Secondary unit-potential free relay  |                 | 100V-120V  | black<br>white US   | 5201006200<br>5201002203  |

| FMS | FMS PLUS | FMS DUAL | MOTOR &<br>CONTROL<br>OPTIONS &<br>ACCESSORIES | ARTICLE  | PACKING<br>UNIT                       |  |                      | ART.NR   |
|-----|----------|----------|--|--|---------------------------------------|--|----------------------|--|
| •   | •        | •        |  | FOREST DIAMOND SENSE REMOTE CONTROL  | 1/box                                 | Works with all<br>Shuttle motors                             | white<br>black       | 5201091470<br>5201096470   |
| •   | •        | •        | **   | FOREST WIRELESS CONNECTOR Incl. 15 cm USB cable / excl USB charger  One way transmitter to control curtains by third party Apps* (i.e. Google / Apple / Amazon) or by Domotics.  *always in combination with Forest smart plug or third party plug   | 1/box                                 | Works with all<br>Shuttle motors                             | white                | 5201002270   |
| •   | •        | •        |  | FOREST WIRELESS CONNECTOR USB PLUG Use in combination with Forest Wireless Connector   | 1/box                                 |  | EU<br>UK<br>AU<br>US | 5201002271-EU<br>5201002272-UK<br>5201002273-AU<br>5201002274-US |
| •   | •        | •        |  | FOREST SMART PLUG WHITE The Forest Smart Plug allows App control via the Forest Connect App (the Forest Wireless Connector is required)  | 1/box                                 | Works with all<br>Shuttle motors                             | EU<br>UK<br>AU<br>US | 5201001952<br>5201001953<br>5201001954<br>5201001955             |
| •   | •        | •        |  | FOREST WIFI DONGLE Incl. cable WiFi 2.4GHz Power supply 12V DC 300mA max USB power 5V DC 1000mA max Control the curtains by Forest Connect App Easy integration third party apps by Google / Amazon Bi-directional   | 1/box                                 | Works with all<br>Shuttle motors<br>except AC and<br>iOn     | white<br>black       | 5201002280<br>5201006280   |
| •   | •        | •        | 0  | FOREST SHUTTLE TWILIGHT SENSOR (KAKU)  | 1/box                                 | Works with all<br>Shuttle motors<br>(besides Shuttle<br>iOn) | white                | 5201001951   |
| •   | •        | •        |  | FOREST WIRELESS WALL SWITCH<br>2-channel wall switch<br>Dimensions: 8.5 x 8.5 x 1 cm   | 1/box                                 | Works with all<br>Shuttle motors                             | white<br>black       | 5201001480<br>5201006480   |
| •   | •        | •        |  | FOREST PULSE WALL SWITCH<br>Can operate one motor only<br>Dimensions: 6.5 x 5.5 x 2.7cm (2.56 x 2.17 x 1.06")  | 1/box                                 |  | white                | 5201001900   |
| •   | •        | •        |  | SHUTTLE CLICK-ON RF MULTI RECEIVER For use with Forest remote in Z-Wave and building autmotion environments  | 1/box                                 |  | white<br>black       | 5201001362<br>5201006362   |
| •   | •        |          |  | FOREST SHUTTLE DEMO FLIGHTCASE METAL Including: Shuttle L with FMS complete, FMS Plus Recess complete, FMS Dual Complete Samples: curved FMS, FMS (White, Grey and Black), MRS, DS-XL motorised, DS-XL LED Motorised, Remote Diamond Sense (White), Wireless Wall Switch (White), WiFi Dongle, Wireless Connector, Forest Smart Plug | Piece                                 |  |                      | 9903000000   |
| •   | •        | •        |  | VELCRO HOTEL PROFILE<br>Inside frame fix, to reduce light leakage in<br>combination with looptape<br>LOOPTAPE  | 120 mtr/<br>bundle<br>25 mtr/<br>roll |  |                      | 3581601600<br>3816202020   |

| FMS | FMS PLUS | FMS DUAL | FMS TRACK +<br>COMPONENTS               | ARTICLE  | PACKING UNIT |   | ART.NR   |
|-----|----------|----------|---|--|--------------|---|--|
| •   |          |          |   | FMS TRACK 5.80 mtr (19') 7.00 mtr (23')   | 10/bundle    | white<br>white<br>matt white<br>grey<br>black<br>matt black | 5101001580<br>5101001700<br>5101007700<br>5101003700<br>5101006700<br>5101008700 |
| •   |          |          |   | FMS CARRIER Klickable, offset, made of UV-resistant plastic. 10 Carriers on a breakaway strip, can be clicked into the the track after installation.                           | 250/box      | white<br>grey<br>black                                      | 2510101000<br>2510103000<br>2510106000   |
|     | •        |          |   | ECONOMY SLIDE<br>Can turn in the track   | 500/box      | white<br>black  | 2510601000<br>2510606000   |
| •   |          |          |   | FMS MASTER CARRIER SHORT R/L WHITE<br>For use with single pleat or pinch pleat curtains<br>For use with one way draw curtains<br>To use in combination with Wave Return Pulley | 25/box       | white<br>black  | 5215801001<br>5215806001   |
| •   |          |          | Marie September 1                       | FMS MASTER CARRIER UNDERLAP CLICK ON<br>Reversible<br>Usable for Click on stiffner   | 15/box       | white<br>matt white<br>grey<br>black<br>matt black          | 5215801010<br>5215801010-M<br>5215803010<br>5215806010<br>5215806010-M           |
| •   |          |          | 50000                                   | FMS MASTER CARRIER OVERLAP CLICK ON<br>Reversible<br>Usable for Click on stiffner  | 15/box       | white<br>matt white<br>grey<br>black<br>matt black          | 5215901010<br>5215901010-M<br>5215903010<br>5215906010<br>5215906010-M           |
| •   |          |          | ( <u> </u>                              | FMS MASTER CARRIER UNDERLAP SINGLE<br>LONG R/L<br>Reversible<br>For single draw curtains   | 15/box       | white<br>black<br>matt black                                | 3016001000<br>3016006000<br>3016006000-M   |
| •   |          |          | (2)                                     | PROLONGED OVERLAP CLICK ON<br>150 mm long<br>200 mm long   | 15/box       | white<br>matt white<br>black<br>matt black                  | 9500001010<br>9500001010-M<br>9500006010<br>9500006010-M                         |
| •   |          |          |   | Z-SHAPED OVERLAP ARM<br>Reversible Z-shaped overlap arm. Fits FMS master<br>carriers. For further reducing of light leakage for<br>center closing.                             | 15/box       | white<br>white  | 9500001020<br>9500001030   |
| •   |          |          |   | STIFFENER CLICK-ON<br>Recommended to attach to the FMS master carriers, stiffner to be stitched into the curtain   | 15/box       |   | 5116001001   |
| •   |          |          | tananananananananananananananananananan | FMS TRANSPORT BELT<br>Toothed belt, to be installed inside the FMS Track   | 100mtr/roll  |   | 5105501000   |
| •   |          |          |   | FMS CONNECTOR To fix the FMS Master Carrier onto the FMS transport belt  | 50/box       | white<br>grey<br>black                                      | 5103011500<br>5103013500<br>5103016500   |
| •   |          |          |   | FMS MOTOR PULLEY<br>Connects motor with FMS Track  | 1/box        | white<br>grey<br>black                                      | 5103011000<br>5103013000<br>5103016000   |
|     |          |          |   | FMS MOTOR PULLEY UPSIDE DOWN   | 1/box        | white   | 5103011003   |
| •   |          |          |   | FMS ANGLE PULLEY 45 degrees adjustable Only for up to 7kg curtain weight (Shuttle M)   | 1/box        | white   | 5103011010   |
| •   |          |          |   | FMS RETURN PULLEY<br>Reverses the FMS transport belt in the FMS track<br>For center draw curtains  | 1/box        | white<br>grey<br>black                                      | 5103011100<br>5103013100<br>5103016100   |
| •   |          |          |   | FMS TRACK JOINER<br>Used to make a solid connection between two<br>pieces of track   | 10/box       | white<br>matt white<br>grey<br>black<br>matt black          | 2518401000-A<br>2518401000-A-M<br>2518403000<br>2518406000<br>2518406000-A-M     |

| FMS | FMS PLUS | FMS DUAL | WAVE<br>COMPONENTS FOR<br>FMS | ARTICLE  | PACKING UNIT |                                 | ART.NR   |
|-----|----------|----------|-------------------------------|--|--------------|---------------------------------|--|
| •   |          |          | alahaha ahahaha               | WAVE ADJUSTABLE MASTER CARRIER UNDERLAP<br>For use with wave pleat curtains (Easyflex)<br>See additional components below  | 25/box       | white<br>black                  | 4813001050<br>4813006050                             |
| •   |          |          |                               | WAVE BELT CONNECTOR CENTER DRAW For use with wave pleat curtains (Easyflex) To use in combination with adjustable wave carrier   | 50/box       | white<br>black                  | 4813001040<br>4813006040                             |
| •   |          |          |                               | WAVE BELT CONNECTOR ONE-WAY DRAW For use with wave pleat curtains (Easyflex) To use in combination with adjustable wave carrier  | 50/box       | white<br>black                  | 4813001030<br>4813006030                             |
| •   |          |          |                               | WAVE RETURN PULLEY MOTORISED For use with wave pleat, single or pinch pleat curtains For wave pleat curtains use in combination with adjustable wave carrier (Easyflex) For single/pinch pleat curtains use in combination with FMS Master carrier short R/L White | 25/box       | white<br>black                  | 4813001060<br>4813006060                             |
| •   |          |          |                               | WAVE DS-XL END STOP To use in combination with adjustable wave carrier Easyflex For center draw curtains   | 100/box      |                                 | 3916001000   |
| •   |          |          |                               | FMS RETURN PULLEY EASYFLEX For use with wave pleat curtains (Easyflex) For single draw curtains  | 1/box        | white<br>grey<br>black          | 5103011102<br>5103013102<br>5103016102               |
| •   |          |          |                               | WAVE ADJUSTABLE HOOK MOTOR For use with wave pleat curtains (Easyflex)   | 25/box       | white<br>black                  | 4813001010<br>4813006010                             |
| •   |          |          |                               | WAVE ADJUSTABLE HOOK RETURN PULLEY For use with wave pleat curtains (Easyflex)   | 25/box       | white<br>black                  | 4813001020<br>4813006020                             |
| •   |          |          |                               | EASYFLEX MASTER CARRIER LEFT For use with wave pleat curtains (Easyflex) For center draw  90 degrees left for small stiffener  | 25/box       | white<br>grey<br>black<br>white | 4815351090<br>4815353090<br>4815356090<br>4815361090 |
| •   |          |          |                               | EASYFLEX MASTER CARRIER RIGHT For use with wave pleat curtains (Easyflex) Center draw  90 degrees right for small stiffener  | 25/box       | white<br>grey<br>black          | 4815451090<br>4815453090<br>4815456090<br>4815461090 |
| •   |          |          |                               | EASYSNAP MASTER CARRIER LEFT For use with wave pleat curtains (Easysnap) 90 degrees  | 15/box       | white                           | 4815301090   |
| •   |          |          |                               | EASYSNAP MASTER CARRIER RIGHT<br>For use with wave pleat curtains (Easysnap)<br>90 degrees   | 15/box       | white                           | 4815401090   |
| •   |          |          |                               | EASYSNAP FMS MASTER CARRIER<br>For use with wave pleat curtains (Easysnap)   | 15/box       | white                           | 4815401000   |
| •   |          |          | 2 2 2 110                     | EASYSNAP FMS UNDERLAP L/R For use with wave pleat curtains (Easysnap)  | 15/box       | white                           | 4815401000   |
| •   |          |          |                               | WAVE STIFFENER CLICK ON 'SMALL' For use with wave pleat curtains (Easyflex/Easysnap) Recommended to attach to the FMS master carriers, stiffner to be stitched into the curtain  | 15/box       | white                           | 4815001001   |

| FMS | FMS PLUS | FMS DUAL | FMS PLUS TRACK +<br>COMPONENTS | ARTICLE  | PACKING UNIT |                     | ART.NR                       |
|-----|----------|----------|--------------------------------|--|--------------|---------------------|------------------------------|
|     |          |          |                                | FMS PLUS TRACK<br>7.00 mtr (23')   | 10/bundle    | white<br>black      | 5131001700<br>5131006700     |
|     | •        |          |                                | 5,80 mtr (19')   | 10/bundle    | matt black          | 5131006580-MAT               |
|     | •        |          |                                | FMS PLUS RECESS PROFILE<br>7.00 mtr (23')  | 1/piece      | white<br>matt black | 5131011100<br>5131016700-MAT |
|     | •        |          |                                | FMS PLUS RECESS PROFILE FIXING STRIP<br>7.00 mtr (23') length  | 1 piece      | white<br>black      | 5131001600<br>5131006600     |
|     | •        |          |                                | FMS PLUS RECESS FIXING WEDGE<br>To fix the track into the recess profile   | 10/box       | white<br>black      | 5131001100<br>5131006100     |
|     | •        |          |                                | FMS PLUS RECESS CORNER TRACK<br>Preshaped 90 degrees curve for FMS PLUS track  | 1/piece      | white               | 5131011790                   |
|     | •        |          |                                | ECONOMY CARRIER Can turn in the track  | 100/box      | white<br>black      | 2510601000<br>2510606000     |
|     | •        |          | (10.33                         | FMS PLUS MASTER CARRIER UNDERLAP<br>Arm is reversible, incl. belt connector<br>For use with wave pleat curtains in combination with<br>FES-system (Easyflex) | 10/box       | white<br>black      | 5135801000<br>5135806000     |
|     | •        |          | 5:03 6:33                      | FMS PLUS MASTER CARRIER OVERLAP<br>Arm is reversible, incl. belt connector<br>For use with wave pleat curtains in combination with<br>FES-system (Easyflex)  | 10/box       | white<br>matt black | 5135901000<br>5135906000-M   |
|     | •        |          |                                | FMS PLUS MASTER CARRIER EASYFLEX L&R<br>90 degrees<br>For use with wave pleat curtains in combination with<br>FES-system (Easyflex)                          | 10/box       | white               | 5135901010                   |
|     | •        |          |                                | FMS PLUS TRANSPORT BELT<br>Toothed belt to be installed inside FMS Plus track<br>9.3 x 2.2mm<br>Material: KEVLAR   | 100mtr/roll  |                     | 5135501001                   |
|     | •        |          |                                | FMS PLUS MOTOR PULLEY<br>Reverse the FMS PLUS belt in the FMS PLUS track   | 5/box        | white<br>black      | 5133011000<br>5133016000     |
|     | •        |          |                                | FMS PLUS RETURN PULLEY<br>Reverse the FMS PLUS belt in the FMS PLUS track  | 5/box        | white<br>black      | 5133011100<br>5133016100     |
|     | •        |          |                                | FMS PLUS MOTOR PULLEY UPSIDE DOWN Can be used to place the motor upside down (recess)  | 1/box        | white               | 5133011003                   |

| FMS | FMS PLUS | FMS DUAL | FMS PLUS TRACK +<br>COMPONENTS | ARTICLE  | PACKING UNIT |                                  | ART.NR   |
|-----|----------|----------|--------------------------------|--|--------------|----------------------------------|--|
|     | •        |          |                                | FMS PLUS L-PULLEY To create a double overlapping track system in combination with only one motor | 1/box        | white                            | 5133011101   |
|     | •        |          |                                | FMS PLUS RECESS COVER PLATE  | 1/box        | white<br>black                   | 5133011104<br>5133016104                             |
|     | •        |          |                                | FMS PLUS RECESS COVER PLATE UPSIDE DOWN Cover plate for recess; motor pulley                     | 1/box        | white<br>black                   | 5133011004<br>5133016004                             |
|     | •        |          |                                | CRS DECO / MRS / FMS PLUS TRACK CONNECTOR<br>Suitable for fms plus with recess profile           | 25/box       |                                  | 5815200005   |
|     | •        |          |                                | FMS PLUS BRIDGE 6,5 cm<br>28 cm  | 10/box       | white<br>black<br>white<br>black | 4518701000<br>4518706000<br>4518601000<br>4518606000 |
|     | •        |          |                                | FMS PLUS TRACK CONNECTOR PIN<br>Stainless steel, 2 x 20mm<br>For a firm seamless connection      | 50/box       |                                  | 990000012  |

| FMS | FMS PLUS | FMS DUAL | FMS DUAL TRACK<br>+ COMPONENTS | ARTICLE  | PACKING UNIT   |                     | ART. NR                      |
|-----|----------|----------|--------------------------------|--|----------------|---------------------|------------------------------|
|     |          | •        |                                | FMS DUAL Two glide track predrilled, aluminium extrusion, white powder coated, lubricated            | 1 length/7 mtr | white<br>matt black | 3851001700<br>3851006700-MAT |
|     |          | •        |                                | FMS DUAL UPPER TRACK CONNECTOR Used to make a solid connection between two pieces of track           | 10/box         | aluminium           | 3851000003                   |
|     |          | •        |                                | FMS DUAL LOWER TRACK CONNECTOR For optimal guiding of the transport belt between two pieces of track | 25/box         | white<br>black      | 3851000002<br>3851006002     |
|     |          | •        |                                | FMS DUAL MOTOR PULLEY<br>Connects motor with track   | 5/box          | white<br>black      | 3851000004<br>3851006004     |
|     |          | •        |                                | FMS DUAL RETURN PULLEY<br>Reverses the transport belt in the track                                   | 10/box         | white<br>black      | 3851000005<br>3851060005     |
|     |          | •        |                                | FMS DUAL ENDSTOP Plastic end stop can be used to set the overlap position                            | 25/box         | white<br>black      | 3851000006<br>3851006006     |
|     |          | •        |                                | FMS DUAL MASTER SET<br>For positioning the 1st carrier   | 10/box         | white<br>black      | 3851000007<br>3851006007     |
|     |          | •        |                                | FMS DUAL TRANSPORT BELT Toothed belt, to be installed inside the track                               | 100 mtr/roll   |                     | 3851000001                   |
|     |          | •        |                                | MCS COVER CAP, 10mm. The cap covers the screw hole and ensures a stylish and ultimate finished look. | 500/box        | white<br>black      | 539999999<br>539999996       |
|     |          | •        |                                | KS ASYMMETRICAL CARRIER  | 500/box        | white<br>black      | 1010001000<br>1010006000     |

| FMS | FMS PLUS | FMS DUAL | MOUNTING<br>OPTIONS +<br>OTHER ITEMS   | ARTICLE   | PACKING<br>UNIT |                                 | ART. NR  |
|-----|----------|----------|--|---|-----------------|---------------------------------|--|
| •   | •        |          |  | SMART KLICK CEILING BRACKET<br>Incl. cover cap<br>'Klicks' onto track, powder coated                  | 100/box         | white<br>grey<br>black          | 1018201001<br>1018203001<br>1018206001               |
|     |          |          |  | ALUMINIUM WALL BRACKET<br>7.5 cm single (3')  | 20/box          | white<br>grey                   | 1020301075<br>1020303075                             |
|     |          |          |  | ALUMINIUM WALL BRACKET<br>10 cm single (4')   | 20/box          | black<br>white<br>grey<br>black | 1020306075<br>1020301100<br>1020303100               |
| •   | •        |          |  | ALUMINIUM WALL BRACKET<br>15 cm double (6')   | 15/box          | white<br>grey<br>black          | 1020306100<br>1020301150<br>1020303150<br>1020306150 |
|     |          |          |  | ALUMINIUM WALL BRACKET<br>20 cm double (8')   | 15/box          | white<br>grey<br>black          | 1020306190<br>1020301200<br>1020303200<br>1020306200 |
|     |          |          |  | ALUMINIUM WALL BRACKET<br>25 cm triple (10')  | 15/box          | white<br>grey<br>black          | 1020306200<br>1020301250<br>1020303250<br>1020306250 |
| •   | •        |          |  | SMART KLICK COVER CAP ALU WALL BRACKET UNIVERSAL  | 50/box          | white<br>grey<br>black          | 1021301000<br>1021303000<br>1021306000               |
| •   | •        |          | 6                                      | FSS MOUNTING BRACKET For concealed installation or ceiling installation in narrow spaces. Heavy Duty. | 100/box         |                                 | 7160001000   |
| FMS | FMS PLUS | FMS DUAL | BENDING<br>COMPONENTS +<br>OTHER ITEMS | ARTICLE   | PACKING<br>UNIT |                                 | ART. NR  |
| •   | •        |          |  | CONTRACT BENDING TOOL BASIC for FMS and FMS Plus  | 1/each          |                                 | 2560000000   |
|     |          |          |  | FMS CONTRACT BENDING WHEEL radius 20 cm incl. wedges  | 1/each          |                                 | 2561000000   |

| FMS | FMS PLUS | FMS DUAL | BENDING COMPONENTS + OTHER ITEMS | ARTICLE   | PACKING<br>UNIT |              | ART. NR                  |
|-----|----------|----------|----------------------------------|---|-----------------|--------------|--------------------------|
| •   | •        |          |                                  | CONTRACT BENDING TOOL BASIC<br>for FMS and FMS Plus                                 | 1/each          |              | 2560000000               |
|     |          |          |                                  | FMS CONTRACT BENDING WHEEL radius 20 cm incl. wedges                                | 1/each          |              | 2561000000               |
|     |          |          |                                  | FMS PLUS CONTRACT BENDING WHEEL ALL-IN radius 20 cm incl. wedges and bending strips | 1/each          |              | 5131000000               |
| •   |          |          |                                  | FMS BENDING STRIPS<br>90 cm<br>T-bending strip                                      | 1/each          |              | 5160100000               |
|     | •        |          |                                  | FMS PLUS SET BENDING STRIPS<br>90 cm  | 1/each          |              | 5131000001               |
|     |          |          |                                  | BENDING STAND<br>Stand for contract bending tool                                    | 1/each          |              | 2560800000               |
| •   | •        |          |                                  | ELECTRIC POWERED BENDER   | 1/each          | 230V<br>110V | 1060500000<br>1060500001 |
|     |          |          |                                  | FMS BENDING WHEEL for electric bender, set of 3                                     | 1/set           |              | 2560700000               |
|     |          |          |                                  | FMS PLUS BENDING WHEEL for electric bender, set of 3                                | 1/set           |              |                          |
| •   |          |          |                                  | FMS/CS BENDING STRIP<br>for electric bender<br>700 cm                               | 1/each          |              | 5160100010               |
|     | •        |          |                                  | FMS PLUS BENDING STRIPS<br>for electric bender                                      | 1/piece         |              | 5160800000               |
| •   | •        | •        |                                  | FOREST LUBRICANT<br>To lubricate components during assembly                         | 1/box           |              | 5109010000               |



